

# Challenger

## 3400

### Standard Features

Five Section Tower Mast.  
 Double Acting Hydraulic Cylinder.  
 4' x 12' Fiberglass Work Platform.  
 5000 Volt Rating. (5 KV)  
 1000 lb. Platform Capacity.  
 42" Folding Hand Rails.  
 360 Degree Full Rotation.  
 Electric/Hydraulic Open Center Full Hydraulic System.  
 5-Air Operated Platform Controls.  
 Deadman Safety Lockout Feature.  
 Emergency Override Feature.  
 Painted Steel- Gloss Black  
 Fiberglass Platform-Natural Green.  
 Meets or exceeds ANSI A92.2 (1990) and OSHA Standards.

### Minimum Chassis GVWR

84" Cab to Axle.  
 Front Axle - 8000 lb.  
 Rear Axle - 15,000 lb.

### Optional Equipment

Outriggers (required on 3435 model)  
 Oversized & Offset Platforms.  
 Remote Controls ( Start-Stop, Emergency Power, etc.)  
 Hydraulic or Air Tool Outlets @ Platform.  
 Reinforced Rails & Rail Cutouts.  
 Ladders for access: Fixed or Telescoping.  
 Special Paint.

**Note:** For detailed specifications or additional Information, contact your local **Challenger Dealer @ 952-938-5451.**

Challenger Aerial Towers from:

**ABM Equipment & Supply**  
 333 2nd Sreet NE  
 Hopkins, MN 55343  
 Phone: 952-938-5451  
 Fax: 952-938-0159

Distributed by:

