



SPAULDING MFG., INC.

5366 EAST ROAD SAGINAW, MI 48601 | PHONE: 989-777-4550 | FAX: 989-777-7430

SLIP-IN TECHNICAL DATASHEET

- 2,4,6, & 8 TON CAPACITY
- (2) 105,000 MINIMUM BTU DIESEL OR PROPANE FUEL SOURCE
- AUTOMATIC TEMPERATURE CONTROL
- 12 VOLT BATTERY
- HYDRAULIC POWERED REAR DOOR (4 TON AND UP)
- BI-FOLD HYDRAULIC TOP DOORS (4 TON AND UP)
- CONTINUOUS WELDS
- HYDRAULIC FLUID SUPPLIED BY TRUCK THROUGH QUICK DISCONNECT
- HOPPER - FULLY INSULATED
- TRIPLE WALL CONSTRUCTION
- HOPPER FLOOR 1/4" STEEL
- FLOOR, AND ALL FOUR WALLS ARE HEATED
- 10 GAUGE CAPPING CHANNEL AND CORNER MOLDING TO ADD STRUCTURAL INTEGRITY TO THE HOPPER PREVENTING IT FROM BECOMING OUT OF SQUARE
- ALL WIRING EXTERNAL TO HOPPER
- PAINT: SANDBLASTED WITH TWO COATS OF EPOXY PRIMER AND URETHANE FINISH
- LENGTH: VARIES BASED ON HOPPER CAPACITY
- WIDTH: VARIES BASED ON HOPPER CAPACITY
- HEIGHT: VARIES BASED ON HOPPER CAPACITY
- NATM COMPLAINT
- OPERATING CONTROLS LOCATED ON CURBSIDE WHEREVER POSSIBLE
- OPTIONAL * BELT DRIVE HOPPER
- OPTIONAL * AUGER DRIVE HOPPER



*6 TON DUAL AUGER SLIP-IN



*6 TON SLIP-IN WITH OPTIONAL STANDING LEGS



* STANDARD 2 TON SLIP-IN