



Spaulding Mfg., Inc.

SPAULDING MFG., INC.

5366 EAST ROAD SAGINAW, MI 48601 | PHONE: 989-777-4550 | FAX: 989-777-7430

TRUCK MOUNT TECHNICAL DATASHEET

- 2.3 & 4 TON CAPACITY
- (2) 105,000 MINIMUM BTU DIESEL OR PROPANE FUEL SOURCE
- AUTOMATIC TEMPERATURE CONTROL
- 12 VOLT BATTERY
- HYDRAULIC POWERED REAR DOOR (4 TON AND UP)
- BI-FOLD HYDRAULIC TOP DOORS (4 TON AND UP)
- CONTINUOUS WELDS
- HYDRAULICS POWERED BY PTO FROM TRUCK
- HOPPER - FULLY INSULATED
- TRIPLE WALL CONSTRUCTION
- HOPPER FLOOR 1/4" STEEL
- FLOOR, AND FOUR WALLS ARE HEATED
- 10 GAUGE CAPPING CHANNEL AND CORNER MOLDING ADD STRUCTURAL INTEGRITY TO THE HOPPER PREVENTING IT FROM BECOMING OUT OF SQUARE
- ALL WIRING EXTERNAL TO HOPPER
- PAINT: SANDBLASTED WITH TWO COATS OF EPOXY PRIMER AND URETHANE FINISH
- 2 TON GVWR OF 7,000 LBS.
- 3 & 4 TON GVWR OF 14,000 LBS.
- LENGTH: 14' - 18'
- WIDTH: 88"
- HEIGHT: VARIES BASED ON HOPPER CAPACITY
- NATM COMPLIANT
- OPERATING CONTROLS LOCATED ON CURBSIDE WHEREVER POSSIBLE
- OPTIONAL *BELT DRIVE HOPPER
- OPTIONAL * AUGER DRIVE HOPPER
- OTHER OPTIONS AVAILABLE



* 6 TON SCISSOR HOIST



* 6 TON SCISSOR HOIST



*6 TON AUGER DRIVE